

Part Number	Package	Configuration	Polarity	V _{DS}	I _D @25°C	R _{DS(ON)} @V _{GS}		R _{DS(ON)} @V _{GS} =4.5V		R _{DS(ON)} @V _{GS} =2.5V		R _{DS(ON)} @V _{GS} =1.8V		V _{GS(TH)}		Qg	Ciss	产品线交货 leadtime	MPQ (最小包装)	SPQ (标准包装)	MOQ (最小订单)	主要竞争对手 料号(国内)	主要竞争对手 料号(国外)
				Max	Max	Typ	Max	Typ	Max	Typ	Typ	Min	Max	Typ	Typ								
				(V)	(A)	(mΩ)	(mΩ)	(mΩ)	(mΩ)	(mΩ)	(mΩ)	(V)	(V)	(nC)	(pF)								
CRM10QT500S	T2 Module	Half-Bridge	N	100	500	0.8	1	1.1	1.3			2.4	3.6	552	27680	4-6W	10	300	300				
CRM10QM80F	MDIP18	3-Phase Full Bridge with NTC	N	100	80	1.9	2.3					2	4	230	11435	4-6W	12	864	144				
CRM20QN500S	N2 Module	Half-Bridge	N	200	500	2.2	2.6	5.8	7			2.4	3.6	279	31533	4-6W	10	200	200				
CRM15QN600S	N2 Module	Half-Bridge	N	150	600	1.1	1.3					2	4	277	20817	4-6W	10	200	200				